

## Catalytic Hydrogen Gas Monitor Specifications

	Target Gas	Hydrogen (in air)
	Sensor Type	Catalytic (with filter)
	Detection range	0 – 25,000 ppm
	Resolution	~100 ppm
	Visual indication	Bi-color LED (red/green)
	Options	Relay, beeper, harness
	Signal types (1)	0-3VDC, 4-20mA, 'TTL'
	Enclosure	Anodized aluminum
	Connector	Molex Mini-fit Jr. 6-pin
	Weight	80g
All dimensions in mm		
Manufactured in Canada		

Parameter	Min.	Typ.	Max.	Units	Notes
Accuracy	5	3	-	%	Percent range, still air
Linearity	5	3	-	%	Percent range, still air
Air Velocity Error		1	1.5	%	Percent range, 3 m/sec
Oxygen Requirement	5	21	-	%	
HMDS Tolerance	100/50 10/500	-	-	ppm/hrs	
Operating Temperature	-40	-	+80	Deg. C	
Operating Humidity	0	-	99	%RH	Non-condensing
Warm-up Time	-	2	10	Secs	
Response Time (T90)	-	2	3	Secs	
Recovery Time (T10)	-	5	10	Secs	
Input Voltage	5	-	40	VDC	Option I2 – switch mode PSU
Power Consumption	-	950	1100	mW	
Output Signal (Optional)					
<u>0-3VDC:</u>					
Trouble Threshold	-	60	-	mV	3mA load max. 0V during fault state
Step Size	-	12	-	mV	Per 100 ppm H <sub>2</sub>
<u>4-20mA:</u>					
Step size	-	0.08	-	mA	Per 120 ppm H <sub>2</sub>
Load	750	-	10	Ohms	750R: Input voltage > 17VDC
<u>Digital</u>					
Low Level	-	-	0.2	V	5mA load max.
High Level	2.0	-	-	V	
Relay (Optional)					Sealed, SPST, NO or NC
Switch Voltage	-	-	200	V <sub>RMS</sub>	
Switch/Carry Current	-	-	0.5/1.2	Amps	
Contact Resistance	-	-	0.15	Ohms	
Insulation Resistance	10 <sup>10</sup>	-	-	Ohms	
Beeper (Optional)	72	78	-	dB	At 30cm
Interface Harness (Optional)	10	15	50	cm	24AWG color-coded wire

These specifications are subject to change without notice. Neodym Technologies Inc. makes no warranties or representations, whether express or implied, about the suitability of this product for any application.